



- NOTES:
- 1 - TOLERANCE  $\pm 0.4$ mm UNLESS STATED
  - 2 - ENVIRONMENTAL TEMPERATURE -40 TO +85 DEG. C
  - 3 - ALL MATERIALS ARE UL94 V0. MAXIMUM TEMPERATURE ON CIRCUIT BREAKER IS LIMITED TO THE PLASTIC MATERIAL IN THE SHELL. MATERIAL IS AMPAL MPV 2000 RTI VALUE IS 130 DEG. FOR 20,000 HOURS

A	DCN 2002029 FIRST ISSUE	GD
REV	DESCRIPTION	SIGN
	MATING FACE	-MF
	PROCESS DIMENSION	-PD
	INTERSECTION	-INT
	BEFORE PLATING	-BP
	ALL DIMENSIONS IN	-mm
	TOLERANCES ON UN-DIMENSIONED 90° FEATURES ARE $\pm 0.5^\circ$	
	TOLERANCES $< \pm 0.1$ ARE CRITICAL	
	BRACKETED DIMENSIONS-EXISTING TOOLING	
	SURFACE AREA	N/A mm <sup>2</sup>
	VOLUME	N/A mm <sup>3</sup>
	MATERIAL	N/A
	RAW MTL No.	N/A
	FINISH	N/A
DRAWN	GD	DATE 06/02/2020
CHECK	RS	APPD RS
TOLERANCES	DO NOT SCALE	
X	$\pm 0.5$	ORIGINAL SIZE A3
X.X	$\pm 0.1$	
X.XX	$\pm 0.05$	
ANGULAR	$\pm 0.5^\circ$	

TITLE  
DD FRAME STD HANDLE  
RAIL MOUNT SCREW TERM



ALL INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF CBI AND IS TO BE TREATED AS CONFIDENTIAL, DISCLOSURE TO THIRD PARTIES IS NOT PERMITTED.

DRG. No. 3990A977  
UG